

# JavaScript Introduction

Topics discussed this presentation

---

- Brief introduction to and history of language
- Roles of the language
- Its data types
- JavaScript Object Notation (JSON)
- Simple program employing JavaScript

# Javascript

## Overview

---


- Originally a small language
- Not anymore - now enormous
- Flawed but powerful
- Not **Java**
- Not a subset of Java
  - Very different languages
- Shares C-family syntax
- Similarities Scheme & Self
- Scores of *badly written books aimed at the dummies and amateur market*




# Javascript

## Language specification growth

**ECMAScript**, Growth in language complexity as measured by increase in successive specification versions.



Standard ECMA-262	
VERSION	SPECIFICATION PAGES
ES1(1997)	100
ES2(1998)	117
ES3(1999)	188
ES5(2009)	250
ES6(2015)	566




# Ecma International

ECMAScript - the language of the web

---

- ECMAScript: standardization body
- Several popular implementations:
  - JavaScript
  - JScript
  - ActionScript
- Edition 6 (ES6) published June 2015
  - Course applies ES6



# JavaScript

Several frameworks available

---


- Client-side
  - Angular
  - Backbone
  - Ember
  - Aurelia
  - React
- Server-side (node)
  - hapi
  - express
  - koa
  - sails
- MEAN stack collection:
  - MongoDB
  - Express.js
  - Angular
  - Node.js



# Nature of JavaScript

## Structure Client-Side Web

---



- Markup (HTML)
- Structure
- Content
- Style (CSS)
  - Style
  - Presentation
  - Appearance
- Function (Javascript)
  - Actions
  - Manipulations

# Nature of JavaScript

## The Language

---

Although not Java, has:

- Similar syntax & keywords
  - Similar standard library naming conventions

Object oriented but does not have classes in classical sense.

- uses *syntactic sugar* to simulate classes
- prototypal: objects inherit from objects

Dynamic typing

- Variable may be reference to object of any type

# Javascript Styling

Our choice from several available Style Guides and IDEs

---

## Airbnb JavaScript Style Guide() {

*A mostly reasonable approach to JavaScript*

[downloads 649k/month](#) [downloads 563k/month](#) [gitter](#) [Join chat](#)

Other Style Guides

- [ES5 \(Deprecated\)](#)
- [React](#)
- [CSS-in-JavaScript](#)
- [CSS & Sass](#)
- [Ruby](#)

### Table of Contents

1. Types
2. References
3. Objects
4. Arrays
5. Destructuring
6. Strings
7. Functions
8. Arrow Functions
9. Classes & Constructors
10. Modules
11. Iterators and Generators
12. Properties
13. Variables
14. Utilities




- *Airbnb JavaScript Style Guide*
- *WebStorm JavaScript IDE*

# Nature of JavaScript

## The Language

---

- Provides access to main components web page:
  - Cascade Style Sheet (CSS) properties
  - Markup content (e.g.: div, img, p)
  - Forms (Communication to server)
- Most often used client-side
- Growing use server-side (node.js)
- Weakly typed with first-class functions
  - function: block reusable code (more on this later)
  - functions are objects
  - may be passed as parameters



# Javascript

## Primitive Data Types

---

- Six primitive types
  - **boolean**
  - **number**
  - **string**
  - **null**
  - **undefined**
  - **symbol** (ES6)
- All other types are **objects**

```
console.log('This is a string');
console.log('true is a boolean');
console.log('10.5 is a number');
```

# Javascript

## Primitive Wrapper Data Types

---

- Four wrapper types
  - **Boolean**
  - **Number**
  - **String**
  - **Symbol**

```
// Wrapper's valueOf returns primitive value.  
const b = Boolean(true); // b => true.
```

# **var, const and let**

---

**var, const and let** used to store values and object references:

- **var** exists since ES1.
- **const & let** introduced ES6.
- Significant behavioural differences.
- Preference given henceforth to use of **const**, then **let**.
- **var** usage should be avoided.

```
var x = 10; // Avoid future use  
let y = 20; // Use where reassign likely  
const z = 30; // cannot be reassigned
```

# Data types

## boolean

---

- boolean can be
  - true
  - false

```
// Output: b is true
const b = true;
if (b) {
    console.log('b is true');
};
```

```
// Ouput: b is true
const b = true;
if (b) {
    console.log('b is', Boolean(b));
};
```

# Data types

## number

---

- *number* 64-bit floating point
  - Similar to Java's *double*
  - No integer type
  - *number* type includes
    - NaN
    - Infinity
  - Problematic in finance
    - $0.1 + 0.2 == 0.3$
    - This expression *false*

```
// Output is 3.333333333333335
const val = 10 / 3;
console.log(val);
```

```
// Output: true. val is not a number
const val = '2005/12/12';
console.log(isNaN(val)); // true
// Output: string
console.log(typeof val);
```

```
const val = 10 / 0;
console.log(val); // Infinity
console.log(typeof val); // number
```

# Data types

## string

---

- *string* sequence of zero or more Unicode characters.
  - Similar to Java *String*.
  - No *char* type as in Java.
  - Literals use ' or " to enclose characters
    - Either quote type may be used in pairs.
    - Illegal to mix.
  - **Important:** Use only single quotes to comply with style guide.

'This is a string.'

"This is also a string but we will not use double quotes."

"This is not a legal string'

# Data types

## string

---

- Internal quotes
- Can use escape sequence \

```
const s = 'What\'s a \"celeb\" famous for?';  
  
// What's a "celeb" famous for?  
console.log(s);
```

# Data types

## null & undefined

---

- Variable not assigned a value is of type **undefined**
- **null** indicates the absence of a value
- Some experienced developers no longer use *null*.

```
var planes; // => undefined  
// A language error in ES5, fixed ES6  
console.log(typeof planes); // => object in ES5
```

```
const planes;  
// SyntaxError: Missing initializer in const declaration
```



# Data types

## symbol

---

### Associated wrapper class **Symbol**

- Introduced in ES6
- Can generate unique property keys
- Eliminates risk collision

```
let uniqueKey = Symbol();
obj = {};
obj[uniqueKey] = 'unique';
console.log(obj[uniqueKey]); // => unique
console.log(uniqueKey); // => Symbol()
console.log(typeof(uniqueKey)); // => symbol
```

# Data types

## Object

---

### Object literal

- comma-separated list of colon-separated name:value pairs in curly braces.

```
const book = {  
    title: 'Java',  
    author: 'Chapman',  
    ISBN: 'ISBN-10 03219804333',  
    edition: 4,  
    isInPrint: true,  
};
```

```
book.isInPrint // => true
```

# Data types

## Object

---

Container comprising

- name-value pairs
- value may be object
- may add new properties anytime

```
▼ Watch Expressions + C
  ▼ book: Object
    ▼ author: Object
      name: "Simpson"
    ► __proto__: Object
    isbn: "ISBN-10 03219804333"
    title: "Java"
  ► __proto__: Object
```

```
const book = {
  title: 'Java',
  author: {
    name: 'Simpson',
  }
};
console.log(book.title); // => Java
```

```
// Add new property (name-value pair)
book.isbn = 'ISBN-10 03219804333';
```

# Semicolon insertion

Example where positioning of curly brace matters

---

```
function myFunction() {  
    return ←  
    {  
        status: true  
    };  
};
```

Semi-colon silently inserted  
following **return**  
keyword has unintended  
consequences:  
returned value is **undefined**.

```
console.log(myFunction()); // undefined
```

# Semicolon insertion

Example where positioning of curly brace matters

---

```
function myFunction() {  
    return {←  
        status: true  
    };  
};
```

K&R style, put the { at the end of a line instead of the front, because *it avoids a horrible design blunder in JavaScript's return statement. (Crockford)*

```
console.log(myFunction()); // Object{status:true}
```

# JavaScript

## Run Program - Simple Example

---

```
/**  
 * A Web Page with HTML & reference to external JavaScript file  
 */  
<!DOCTYPE html>  
<html>  
  <head>  
    <meta charset="UTF-8">  
  </head>  
  <body>  
    <h1 id="hello">Hello ICTSkills</h1>  
    <script src="js/foo.js"></script>  
  </body>  
</html>
```

# JavaScript

## Run Program - Simple Example

---


```
/**  
 * Demo JavaScript code  
 */  
alert('Hello ICTSkills');  
function foo() {  
    const size = 3;  
    for (let i = 0; i < size; i += 1) {  
        console.log(i);  
    }  
}  
  
foo();
```

# JavaScript

## Run Program - Simple Example


---

# Hello ICTSkills



# JavaScript

## Run Program - Simple Example



# JavaScript

## Run Program - Simple Example

The screenshot shows a code editor interface with the following details:

- Project View:** A sidebar on the left displays a project named "js-lab-1" containing "step-1.html" and "step-1.js".
- step-1.html:** The main editor tab contains the following HTML code:

```
1  <!--Attempting to access an element too early will have unexpected results.-->
2  <!DOCTYPE html>
3  <head>
4      <meta charset="UTF-8">
5      <title>step-1</title>
6      <script src="step-1.js" defer></script>
7  </head>
8  <body>
9      <h1 id="hello-world">Hello World</h1>
10 </body>
11 </html>
```
- step-1.js:** A secondary editor tab contains the following JavaScript code:

```
1  let title = document.getElementById('hello-world');
2  console.log(title);
3
```